



product name		Production location
Cammello Geschaafd MT/ZV/ZA	A4-12	Kessel
Format		
Moulding method		Wirecut
WF71: 204 x 50 x71 mm		Between batches the average size and color may slightly differ.
Essential Characteristics - EN1344		
		
Reaction to fire	A1	
External fire performance	NPD	
Dangerous substances	NL-BSB	
Transverse breaking load	T4	Category
Unpolished slip/skid resistance USRV	U3	Category
Thermal conductivity	NPD	
Durability against freeze thaw	FP100	Category
Sustainable slip/skid resistance	U2	Category
Other Characteristics - EN1344 & BRL 2360		
Paver quality 1	A4-12	Category
Paver quality 1 Tolerances	$\leq 0,4 \sqrt{\text{dimensions}}$	
Paver quality 1 Range	R1	Category
Water absorption	$\leq 5\% \text{ m/md}$	
Abrasion resistance	A2	Category
Acid resistance	C	Category
Other Characteristics - PTV 910		
Standardized Quality Classes	NPD	
Water absorption	NPD	
		
Storage & handling		Cutting
<ul style="list-style-type: none"> - Stock pavers on a clean surface and cover them - Blend from different pavers (pack) at the same time - Do not clean fresh masonry with hydrochloric acid 		Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).